



# CAPRICHEM (Pty) Ltd.

*Committed  
to  
Service*

SPECIALISTS IN INDUSTRIAL CHEMICALS & CONTRACT MANUFACTURING

## FLOOR MAINTENANCE PROGRAM

Product	Equipment	Dilution	Application
<b>W.C.T SEALER</b> ACRYLIC FLOOR SEALER		Apply undiluted	<ul style="list-style-type: none"> <li>Strip, rinse &amp; dry before sealing</li> <li>Using lambswool applicator spread thinly &amp; evenly, working towards the door</li> <li>Allow to dry completely between coats</li> <li>Apply 2 coats</li> </ul>
<b>DIAMOND GLOW EEZY SHINE FLOOR SHINE</b> ACRYLIC FLOOR POLISH		Apply undiluted	<ul style="list-style-type: none"> <li>Sweep or vacuum first</li> <li>Using lambswool applicator spread thinly &amp; evenly, working towards the door</li> <li>Allow to dry completely before applying next coat</li> <li>After applying 3 coats, allow to dry for 24 hours before buffing</li> </ul>
<b>SPRAY BUFF</b> BUFFING COMPOUND FOR SEALED FLOORS		Dilute 200ml to 800ml water	<ul style="list-style-type: none"> <li>Sweep or vacuum first</li> <li>Spray lightly onto floor</li> <li>Use a buffing pad</li> <li>Buff with machine</li> <li>Buff small areas at a time</li> </ul>
<b>MOP &amp; BUFF</b> MOPPING COMPOUND FOR SEALED FLOORS		Dilute up to 1 litre to 40 litres water	<ul style="list-style-type: none"> <li>Sweep or vacuum first</li> <li>Using a mop or polymer applicator, apply diluted solution and buff if necessary</li> </ul>
<b>FLOOR MAINTAINER</b> CLEANING COMPOUND FOR SEALED FLOORS		Dilute up to 1 litre to 40 litres water	<ul style="list-style-type: none"> <li>Sweep or vacuum first</li> <li>Using a mop, clean the floor with solution</li> <li>Rinse floor thoroughly</li> <li>Allow to dry</li> </ul>
<b>T-STRIP</b> NON AMMONIATED POLYMER STRIPPER		Dilute 1 litre to 6 litres water	<ul style="list-style-type: none"> <li>Sweep or vacuum first</li> <li>Dilute stripper with warm water and apply to floor</li> <li>Leave for 10 minutes</li> <li>Scrub with black stripping pad</li> <li>Mop up or wet vacuum</li> <li>Rinse with clean water twice</li> <li>Allow to dry</li> </ul>
<b>AMMOSTRIP</b> AMMONIATED POLYMER STRIPPER		Dilute 1 litre to 5 litres water	<ul style="list-style-type: none"> <li>Sweep or vacuum first</li> <li>Dilute stripper with warm water and apply to floor</li> <li>Leave for 10 minutes</li> <li>Scrub with black stripping pad</li> <li>Mop up or wet vacuum</li> <li>Rinse with clean water twice</li> <li>Allow to dry</li> </ul>







# CAPRICHEM (Pty) Ltd.

*Committed  
to  
Service*

SPECIALISTS IN INDUSTRIAL CHEMICALS & CONTRACT MANUFACTURING

## FLOOR MAINTENANCE EQUIPMENT

Floor Pad	Description	Application	Size
	<b>Black High Performance Stripping Floor Pad</b>	For rapid, heavy duty stripping. Removes floor finish build-up quickly	400mm 425mm 450mm 500mm
	<b>Blue Scrubbing Floor Pad</b>	For heavy duty scrubbing or light stripping. Removes the soiled top layer of floor finish.	400mm 425mm 450mm 500mm
	<b>Red Buffing Floor Pad</b>	For spray buffing or light scrubbing. Removes scuff marks and soil while producing a smooth finish.	400mm 425mm 450mm 500mm
	<b>White Polishing Floor Pad</b>	For polishing. An extra fine pad that produces a high lustre finish.	400mm 425mm 450mm 500mm

