



CAPRICHEM *Committed to Service* (Pty) Ltd.

SPECIALISTS IN INDUSTRIAL CHEMICALS & CONTRACT MANUFACTURING



STEAM-L
Low Foaming Liquid

STEAM-L

Low Foaming Liquid

DESCRIPTION

STEAM-L is a low foaming liquid compound, used for general purpose steam cleaning. STEAM-L contains degreasing solvents, detergents, wetting agents, rinse additives and is also a corrosion inhibitor.

APPLICATION

STEAM-L can be used through a steam cleaning unit for the cleaning of carpets, upholstery, engines, metal structures, etc.

DIRECTIONS FOR USE

Carpet Cleaning – use 100ml of STEAM-L to 20lts of water.

Heavily Soiled Areas – use a stronger concentrate e.g. 100ml STEAM-L to 10lts of water.

Engines, metal parts, structures, tanks, etc. either soiled with oil, grease or food residues - use 1l of STEAM-L to 50lts of water.
Light Duty Steam Cleaning – dilute 100:1 which will be sufficient.

After steam cleaning rinse cleaned areas with tap water.

ADVANTAGES

Economical to use
Low foaming
Safe on all metals
Free Rinsing

CAUTION

Avoid any contact with skin and eyes, contains solvents and degreasing agents. Do not mix with any other detergents, as the cleaning properties of STEAM-L might be impaired.

PACKING

STEAM L is packed in 5 Litre and 25 Litre containers.

NOTICE TO THE READER: The information and recommendations presented on this data sheet are to the best of our knowledge and belief accurate and reliable, but do not constitute a warranty. None of our representatives or agents are authorised to give any guarantee or warranty or make any representation in addition or contrary to the above, and we do not accept liability of any kind for any loss including, without limitations, consequential loss, injury or damage arising from the use of the information or recommendations, or of the products which are subject to the subject matter hereof. These products are sold to our standard condition of sale and tender, copies of which are available on request.

PO Box 160, Blackheath 7581, 6 Gooderson Road, Blackheath 7580, Email info@caprichem.com, Tel 021 905 4712, Fax 021 905 4718



Robert Jonas (Managing Director), Reg. No. 1998/016011/07, Vat No. 4640180149

www.caprichem.com