



CAPRICHEM

*Committed
to
Service*

(Pty) Ltd.

SPECIALISTS IN INDUSTRIAL CHEMICALS & CONTRACT MANUFACTURING



W.C.T. SEALER
Acrylic Floor Sealer

WIZARD W.C.T. SEALER 25%

Acrylic Floor Sealer

DESCRIPTION

A 25% Acrylic Emulsion base coat that is applied directly over the floor surface under the layers of emulsion floor polishes. It is formulated for use as a primer or sealer that will give your floors the perfect foundation and permanent protection, against chemical spills, stains and scuff marks. Provides a hard, durable, non-removable base coat that will extend the life of your floors. It has outstanding resistance to discolouration during the floor polish ageing process.

ONLY USE ON CLEAN DRY FLOORS / USE INDOORS OR OUTDOORS.

USES

Safe to use on Vinyl, Rubber, Linoleum, Terrazzo, Marble, Slate, Quarry tiles, Sealed wood and Asphalt floors.

FLOOR PREPARATION

Remove all old sealers, waxes, coatings and soil by hand or machine scrubbing, always using a black scrubbing pad. Use WIZARD W.C.T. STRIPPER, WIZARD AMMOSTRIP or WIZARD T-STRIP for stripping. Rinse twice thoroughly with clean water and allow the floor to dry properly. Leave no RESIDUE on the floor. NEVER APPLY WIZARD W.C.T. SEALER OVER A TOP COAT FINISH.

APPLICATION

Using only clean applicators and buckets, apply WIZARD W.C.T. SEALER over clean dry floor in thin, even, parallel strokes using a clean lambswool applicator or lint free cloth. DO NOT RUB OR ALLOW TO PUDDLE. Allow adequate time to dry thoroughly (approximately 1 hour) before applying the second and third coats in the same way. Normally only two coats are required, but a third and a fourth coat would give greater durability. This will form the solid foundation for a good maintenance program. DO NOT APPLY SECOND COAT BEFORE FIRST COAT IS PROPERLY DRY.

MAINTENANCE

Sweep or vacuum the floor first to remove loose dust or dirt by damp or wet mopping where necessary, using WIZARD FLOOR MAINTAINER. Always wipe up spills immediately.

COVERAGE

1 Litre WIZARD W.C.T. SEALER 25% covers approximately 30 - 60m² per coat depending on the porosity and absorbency of the floor.

PRECAUTIONS

Never apply WIZARD W.C.T. SEALER over a top coat finish. Floor must be clean and dry before sealer is applied. Always use clean equipment and applicators and wash thoroughly before storing away.

PERSONAL PROTECTIVE WEAR / FIRST-AID MEASURES

EYE CONTACT

Symptoms: Causes mild eye irritation.

Prevention: Safety glasses could be worn.

First-aid: Immediately flush eyes with water for at least 15 minutes and get medical attention if irritation persists.

SKIN CONTACT

Symptoms: Prolonged or repeated contact may cause dry skin and irritation.

Prevention: Rubber or Neoprene gloves and additional impervious protective clothing should be worn.

First-aid: Wash with soap and water.

INHALATION

Symptoms: None known.

Prevention: None known.

First-aid: Seek medical attention.

INGESTION

Symptoms: None known.

Prevention: Store away from food stuffs.

First-aid: Seek medical attention immediately.

PACKING

WIZARD W.C.T. SEALER is packed in 2 Litre, 5 Litre and 25 Litre containers.

For more information revert to the detailed technical data sheet.

NOTICE TO THE READER: The information and recommendations presented on this data sheet are to the best of our knowledge and belief accurate and reliable, but do not constitute a warranty. None of our representatives or agents are authorised to give any guarantee or warranty or make any representation in addition or contrary to the above, and we do not accept liability of any kind for any loss including, without limitations, consequential loss, injury or damage arising from the use of the information or recommendations, or of the products which are subject to the subject matter hereof. These products are sold to our standard condition of sale and tender, copies of which are available on request.

PO Box 160, Blackheath 7581, 6 Gooderson Road, Blackheath 7580, Email info@caprichem.com, Tel 021 905 4712, Fax 021 905 4718



Robert Jonas (Managing Director), Reg. No. 1998/016011/07, Vat No. 4640180149

www.caprichem.com